



Угольник с наружной резьбой LMS

присоединяет дюймовую трубку к отверстию с цилиндрической резьбой SAE

Размеры в дюймах

Номер детали *	T	S	A	B	C	D	E min	G	H	H1	J Размер шестигр.		Размер уплот. кольца #
											W	#	
4LMS4[]	1/4	7/16-20	1.17	9/16	1/2	.64	.19	.84	.39	1.03	9/16	.66	904
4LMS6[]	1/4	9/16-18	1.31	9/16	13/16	.64	.19	.98	.44	1.25	11/16	.80	906
6LMS6[]	3/8	9/16-18	1.38	11/16	13/16	.72	.30	1.03	.44	1.25	11/16	.80	906
6LMS8[]	3/8	3/4-16	1.41	11/16	1	.72	.30	1.06	.50	1.48	7/8	1.02	908
8LMS8[]	1/2	3/4-16	1.59	7/8	1	.97	.42	1.13	.50	1.45	7/8	1.02	908
12LMS12[]	3/4	1 1/16-12	1.69	1 1/8	1 1/4	1	.66	1.25	.66	1.94	1 1/4	1.44	912
16LMS16[]	1	1 5/16-12	1.88	1 1/2	1 1/4	1.31	.88	1.31	.66	2.05	1 1/2	1.73	916
20LMS20[]	1 1/4	1 7/8-12	2.67	1 7/8	1 11/16	1.62	1.09	1.80	.66	2.29	1 7/8	2.16	920
24LMS24[]	1 1/2	2 -12	3.07	2 1/4	2	1.97	1.34	2	.66	2.38	2 1/4	2.45	924